

Relive the Moment

Vital Moment Reproduced with Exceptional Colors



PhotoVue Photographer Monitor SW321C

To preserve the moment captured, the true colors have to be shown faithfully whether it's on screen or on paper. BenQ Photographer Monitor SW321C offers a wide range of colors with 99% Adobe RGB and 95% DCI-P3/Display-P3 color space to deliver brilliant colors. SW321C also supports HDR to bring you finest details and various video formats to present the real content. Featuring the latest technology, Paper Color Sync, SW321C simulates the photo-printing results to facilitate the photo re-touching process. Keep the moment and never let it fade away.

BenQ

Because it matters

AQCOLOR™

Colors You Can Trust

Industry **STANDARD** | Displaying **DETAILS** | Out-of-the-Box **GUARANTEE**



Industry Color Standards

Enrich Your Palette with 99% Adobe RGB

High color standards by 99% of Adobe RGB, 100% of sRGB/Rec.709, and 95% of DCI-P3/Display P3 result in a more realistic color representation for outdoor and nature photography.

Color Precision with 16 bit 3D (LUT) & Delta E<2

The 16 bit 3D look up table (LUT) and precise Delta E<2 in Adobe RGB and sRGB color spaces render the truest view of the original image with accurate colors.

Color Consistency in Every Detail

Uniformity Technology

BenQ Uniformity Technology fine-tunes the color and brightness of the hundreds of sub-regions across the entire screen and thus offers screen-wide precise color for perfectly authentic and consistent viewing experiences.

Hardware Calibration

Hardware calibration allows you to adjust the monitor's internal image processing chip, keeping displayed images consistent with the original content without being affected by graphic card setting.

Display Every Splendid Scene with Details

HDR for Vibrant Images

SW321C is compatible with HDR10 and HLG formats so that videographers can preview the HDR effect of the video content, ensuring desirable outcomes for their final works.

Video Format Supports Present the Real Content

SW321C supports 24P/25P film content to be displayed at native cadence without pulldown which can distort playback of the source video.

Intuitive Designs for Work Efficiency

Screen-to-Print Consistency

SW321C includes Paper Color Sync software and A.R.T. (Advanced Reflectionless Technology) panels that let photographers easily and efficiently display photo previews that match final prints.



USB-C Port

The latest USB-C™ port provides high-speed video/audio/data transmission and power delivery with one single cable.



- Super Speed USB
- One Cable For Audio / Video / Data
- Power

Hotkey Puck G2

Preferred color modes and features are designated as quick access to widely used settings.



SW321C	
Product Color	Gray
Display	
Screen Size	32"
Aspect Ratio	16 : 9
Resolution (max)	3840 x 2160
Display Area (mm)	708.48 x 398.52
Pixel Pitch (mm)	0.1845
Brightness (typ.)	250
Native Contrast (typ.)	1000:1
Panel Type	IPS
Viewing Angle (L/R/U/D)(CR>=10)	178/178
Response time	5ms(GtG)
Display Colors	1.07 Billion
Color Gamut	99% AdobeRGB 95% P3 100% sRGB
PPI	137
Refresh Rate	60Hz
Backlight Technology	LED
DCR (Dynamic Contrast Ratio)(typ.)	20M:1
Audio	
Headphone Jack	Yes
Monitor	
Color Mode	Adobe RGB sRGB Rec.709 B&W DCI-P3 Display P3 M-book HDR B+W Calibration 1 Calibration 2 Calibration 3 Custom Paper Color Sync DICOM
HDR	HDR10 HLG
Display Mode	Full Aspect Ratio, 1:1
Color Temperature	5000°K 6500°K 9300°K Custom User Defined
Gamma	1.6 - 2.6, sRGB
K Locker	YES
OSD Language	18 Language
PIP/PBP	Yes
HDCP	2.2
VESA Wall Mounting	100x100mm
Dimension & Weight	
Dimensions (H x W x D mm) (w/o Base)(with shading hood)	453.45 x 759.4 x 257.89
Dimensions (H x W x D mm)	H: 664.1 x 759.4 x 340.53 L: 514.1 x 759.4 x 340.53
Dimensions (HxWxD mm)(w/o Base)	448.15 x 747.2 x 77.82
Dimensions (HxWxD mm)(without shading hood)	H: 652.7 x 747.2 x 285.27 L: 504.86 x 747.2 x 285.27
Net Weight (kg)(without shading hood)	12.6
Gross Weight (kg)	26.4
Tilt (down/up)	-5° ~ -20°
Swivel (left/right)	45°/45°
Pivot	90°
Video Signal Data	
Ver. Frequency (KHz)	24~76Hz
Video Bandwidth (M Hz)	600M Hz
Professional	
3D-LUT	16bits
Delta E	≤ 2 (avg)
Uniformity Technology	Yes
Video Format Support	Yes
Gamut Duo	Yes
Black Level	Yes
Hotkey Puck G2	Yes
Factory Calibration Report	Yes
Black & White mode	Yes
Hardware Calibration	Yes
Software	
Palette Master Element	Yes
Connectivity	
USB type-C™	Yes (PD60W, DP Alt mode, Data)
HDMI	HDMI (v2.0)x2
DisplayPort	DisplayPort (v1.4)
Card Reader	SD/MMC type
Power	
Voltage Rating	100~240V
Power Consumption (standby mode)	0.5W
Power Consumption (base on Energy star)	52W
Power Supply	Built-in
Compatibility	
Mac Compatible	Yes
Windows® Compatible	Windows®10 Windows®8.1 Windows®8 Windows®7
Certification	
CalMAN Verified	Yes
Pantone Validated	Yes

*The transmission rate of USB-C™ can vary. *USB-C is compatible with Thunderbolt 3. *Please make sure your laptop's USB-C port supports DisplayPort Alt. mode. * Please make sure the purchased cable is certified by USB-IF and is full-featured with power delivery and video / audio / data transfer functions.

